

BUILDING	CONCRETE	CHORD	DELTA	MANHOLE	RIGHT OF WAY	SQUARE FEET	AIR CONDITIONER	PILE	ANCHOR	WALL	CONCRETE	WATER METER	IRRIGATION CONTROL BOX	FIRE HYDRANT	ELECTRIC BOX	FIBER OPTIC BOX	LIGHT POLE	MEASURED	UNT	RECORDED	CONCRETE MONUMENT
B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W

§ 1436337 (MN 351 171). Commencing at a railroad spur found in the center of the 80-foot, right-of-way of Baldwin County Road No. 49, and being the Northwest corner of Section 3, Township 38S, Range 3E, East, being a distance of 1709.29 feet to a point; thence South 89° 25' 15" East, being a distance of 100.00 feet to an iron pin marker on the first "right-of-way" line of said Baldwin County Road No. 49, being a distance of 100.00 feet to the Point of Beginning; thence along said right-of-way line North 00° 01' 35" East, being a distance of 1494.59 feet to an iron pin marker; thence North 30° 49' 49" West, a distance of 1494.59 feet to the Point of Beginning.

SCALE: 1"=100'

been performed by this firm. The parcel shown hereon is subject to setbacks, zoning, easements, rights or way underground structures, utilities, cemeteries or burial sites were not located unless otherwise noted. Information valid for a period of 6 years from the date of survey and non-transferable.

the search of this
or restrictions v
background portio
survey is intende

... and non-transferable.